

Manual stacker



Model:SDJA1000/SDJA1500

Advantages:

- Robust Steel profile construction.
- An economical lift to handle tasks from transporting dies and moulds skids and pallets.
- Sturdy and compact enough to fit through standard doors and to operate in congested areas.
 - Precision engineered for smooth performance and exceptional durability.
 - Lifting function operated by foot and hand controls.

Main specifications:

Model		SDJA1000	SDJA1500
Load capacity/rated load	Q(kg)	1000	1500
Load centre distance	c(mm)	400/500	400/500
Fork height,lowered	h13(mm)	90	90
Height, mast lowered	h1(mm)	2085/1840	2090
Max. lift height	h3(mm)	1600/2500	1600
Height, mast extended	h4(mm)	2165/2925	2150
Overall length	l1(mm)	1380/1640	1380/1640
Overall width	b1(mm)	1000	1000

Fork dimensions	s/e/l(mm)	30/100/800(1060)	30/100/800(1060)
Distance between fork-arms	b5(mm)	950/700	950
Round clearance, laden,below mast	m1(mm)	25	25
Aisle width for pallets 1000x1200 crossways	Ast(mm)	1580/1840	1580/1840
Aisle width for pallets 800x1200 lengthways	Ast(mm)	1625/1891	1625/1891
Turning radius	Wa(mm)	1235	1235
Lift speed,laden/unladen	mm/time	25	25
Lowering speed,laden/unladen	mm/time	Manual control	
Service weight	kg	250/316	255